



BEARING NO.	d_1 H_7	d_2 Reference	b_1 0 -0.13	α Degrees	b_2 ± 0.3	d_3 ± 0.5	d_5 JIS class 2	h ± 0.5	l_1 ± 0.7	kgf-cm	kgf	g
NOS-3	3	6.8	6	11	4.5	12	M3x0.5	27	15	0.2~3.5	170	6
NOS-4	4	7.6	7	12	5.25	14	M4x0.7	30	17	0.2~3.5	250	10
NOS-5	5	8.8	8	12	6	16	M5x0.8	33	20	0.2~3.5	800	12
NOS-6	6	11.1	9	10	6.75	18	M6x1	36	22	0.2~3.5	880	19
NOS-8	8	12.7	12	12	9	22	M8x1.25	42	25	0.2~3.5	1200	32
NOS-10	10	15.2	14	12	10.5	26	M10x1.5	48	29	0.2~3.5	1700	54
NOS-12	12	17.6	16	12	12	30	M12x1.75	54	33	0.2~3.5	2400	85
NOS-14	14	19.2	19	14	13.5	34	M14x2	60	36	0.2~3.5	2700	126
NOS-16	16	22.7	21	13	15	38	M16x2	66	40	0.2~3.5	3400	185
NOS-18	18	24.1	23	14	17	42	M18x1.5	72	44	0.2~3.5	4700	258
NOS-20	20	28.8	25	12	18	46	M20x1.5	78	47	0.2~3.5	4900	340
NOS-22	22	30.3	28	13	20	50	M22x1.5	84	51	0.2~3.5	5500	435
NOS-25	25	32.4	31	14	22	56	M24x2	94	57	0.2~3.5	7100	730
NOS-28	28	35.7	35	16	26	66	M27x2	110	66	0.2~3.5	8500	1000
NOS-30	30	38.2	37	16	26	66	M30x2	110	66	0.2~3.5	10100	1320

- Materials:**
1. Appearance: S35C Medium Carbon Steel
 2. Steel ball SUJ2 HRC 60+2/-2
 3. NOS Self-lubricated, Teflon, Non oil supply type