



Model NO.	$d_1$ $H_7$	$d_2$	$b_1$ 0 -0.13	$\alpha$	$b_2$ $\pm 0.3$	$d_4$ $\pm 0.5$	$d_5$ JIS2	$h$ $\pm 0.5$	$l_1$ $\pm 0.7$	$d_6$ $\pm 0.5$	$d_7$ $\pm 0.5$	$l_2$ $\pm 0.7$	$w$ $\pm 0.25$	kgf-cm	kgf	g
RBT-3	3	6.8	6	11	4.5	12	M3x0.5	21	10	6.5	8	3	7	0.2~3.5	170	10
RBT-4	4	7.6	7	12	5.25	14	M4x0.7	24	12	8	9.5	4	8	0.2~3.5	250	12
RBT-5	5	8.8	8	12	6	16	M5x0.8	27	14	9	12	4	9	0.2~3.5	800	16
RBT-6	6	11.1	9	10	6.75	18	M6x1	30	14	10	13	5	11	0.2~3.5	880	25
RBT-8	8	12.7	12	12	9	22	M8x1.25	36	17	12.5	16	5	14	0.2~3.5	1200	43
RBT-10	10	15.2	14	12	10.5	26	M10x1.5	43	21	15	19	6.5	17	0.2~3.5	1700	72
RBT-12	12	17.6	16	12	12	30	M12x1.75	50	24	17.5	22	6.5	19	0.2~3.5	2400	107
RBT-14	14	19.2	19	14	13.5	34	M14x2	57	27	20	25	8	22	0.2~3.5	2700	160
RBT-16	16	22.7	21	13	15	38	M16x2	64	33	22	27	8	22	0.2~3.5	3400	210
RBT-18	18	24.1	23	14	17	42	M18x1.5	71	36	25	31	10	27	0.2~3.5	4700	295
RBT-20	20	28.8	25	12	18	46	M20x1.5	77	40	27.5	34	10	32	0.2~3.5	4900	380
RBT-22	22	30.3	28	13	20	50	M22x1.5	84	43	30	37	12	32	0.2~3.5	5500	490
RBT-25	25	32.4	31	14	22	56	M24x2	94	48	33.5	42	12	36	0.2~3.5	7100	870
RBT-28	28	35.7	35	15	24	66	M27x2	110	56	40	40	15	41	0.2~3.5	8500	1180
RBT-30	30	38.2	37	16	25	66	M30x2	110	56	40	50	15	41	0.2~3.5	10100	1450

- Materials:**
1. Appearance: SUS 304C or 303C
  2. Steel ball SUS 440C HRC 58° +2° -2°
  3. RBT Self-lubricated, Teflon, Non oil supply type

- Materials:**
1. Ball 440C Stainless steel
  2. Body 304C or 303C Stainless steel

- Notes:**
1. Teflon liner permanently bonded to the inside diameter of the lathe.
  2. For left screws, please add "L", i.e. RBTL-3